

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
	VOLTAGE	100 V AC	APPLICABLE CONNECTOR	DF19#-*P-1H(56)
	CURRENT	0.5 A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>
---------------------	---------------------------------------	-----------------------	-----------------------	-----------------------

MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>
---------	---------------------	--	-----------------------	-----------------------

--	--	--	--	--

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------	--------------------------	----------	---------	------

<input type="checkbox"/>				
--------------------------	--	--	--	--

REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT. Unless otherwise specified, refer to JIS C 5402.	APPROVED	TY.OMA	06.02.09
	CHECKED	HK.UMEHARA	06.02.09
	DESIGNED	IO.DENPOUYA	06.01.28
	DRAWN	AH.MIYAZAKI	06.01.28

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-311700-01
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DF19G-*S-1F-GND(05)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL685-	<input type="checkbox"/> 1/